

## BK400: Supermoto Master Cylinder & Brake Line Kit Yamaha YZF450F / YZF250F (2006)

### PARTS LIST

- Master Cylinder w/ Graves brake Lever 1
- Front Brake Line 1



<<<<<< IT IS RECOMMENDED THAT THIS PRODUCT BE INSTALLED BY A QUALIFIED TECHNICIAN >>>>>>

- 1) Please be sure the motorcycle is cooled down and safe to work on.
- 2) Bleed the brake fluid from the stock front brake.
- 3) Remove the stock front brake line.
- 4) Remove stock front brake master cylinder.
- 5) Install the new supermoto front brake master cylinder. Adjust to the desired position and torque bolts (9 Nm / 6.5 ft lbs).
- 6) Route the new front brake line through the cable guide and brake hose holder.
- 7) Using new banjo bolt washers, attach brake line to the brake caliper and torque (30 Nm / 22 ft lbs) banjo bolt.
- 8) Attach brake nipple to the brake master cylinder and torque bolt (30 Nm / 22 ft lbs).
- 9) Attach brake line to brake nipple and torque (30 Nm / 22 ft lbs).
- 10) Fill and bleed brake system with brake fluid per the motorcycle manufacturers recommend instructions.
- 11) Check for leaks and test brake system for proper operations.
- 12) **BE SURE BRAKE SYSTEM WORKS PROPERLY BEFORE RIDING MOTORCYCLE!**