

EXD-0798-SSC: w/Carbon Fiber Silencers
EXD-0798-SST: w/Titanium Silencers
Stainless Steel Cat. Eliminator Exhaust System
Ducati 1098 (2007)**PARTS LIST**

<u>ITEM</u>	<u>Part #</u>	<u>QTY</u>	
• Mid-pipe (Left)		1	1
• Mid-pipe (Right)		1	
• Silencer (Left)	ECD0798L	1	
• Silencer (Right)	ECD0798R	1	
• Silencer Straps		2	
• Hanger Strap Pads		2	
• Springs, 63mm	OM.025	4	
• Spacers	28mm	2	
• Bolts	8 x 50mm	2	

<<<<<<PLEASE READ INSTRUCTIONS CAREFULLY BEFORE BEGINNING INSTALLATION >>>>>>

- 1) Be sure the motorcycle is cooled down and safe to work on.
- 2) Remove springs that secure stock mufflers to mid-pipes.
- 3) Remove the hardware that secures the stock mufflers to the subframe. Remove the stock left and right mufflers.
- 4) Install the left and right s-bends. **Do not install springs yet.**
- 5) Using the bolts and spacers provided, install the silencers and silencer straps with rubber liners onto the s-bends. **Do not over tighten the silencer strap, leave loose for now. Do not install the springs yet.**
***Be Careful not to scratch the tail section when mounting Hanger strap.**
- 6) Align the exhaust system by gently rocking the silencers back and forth until centered. This will ensure the exhaust system is not binding and is properly aligned.
- 7) Torque (20 Nm / 14 ft lbs) the hardware for the silencer straps.
- 8) Install all springs.
- 9) Before starting your motorcycle, be sure to clean any finger prints or dirt from your exhaust. If you don't, the heat from running your bike will stain the titanium and/or stainless steel material of your exhaust. Apply a penetrating lubricant (i.e. WD-40 or suitable equivalent) or Rubbing Alcohol to a soft clean rag and wipe down your exhaust system to remove any dirt and fingerprints. Take care not to scratch the system. The heat will burn off the lubricant and create an even bluing effect.
- 10) Before starting engine check again for proper installation/clearance.

