



# FEK-19ZX6-K

7629 Densmore Ave. Van Nuys, Ca. 91406 | 800-867-6480 | www.gravesport.com

<<<< INSTALLATION OF THIS PRODUCT SHOULD BE PERFORMED BY A QUALIFIED TECHNICIAN >>>>  
<<<<<< READ INSTRUCTIONS COMPLETELY BEFORE BEGINNING INSTALLATION >>>>>>

## PARTS LIST

Tag Bracket	1	6mm Nyloc Nuts	4
Right Signal Mount Assembled	1	6mm Bolts	4
Left Signal Mount Assembled	1		

1. Remove passenger seat and tray to access the four fender bolts.
2. Locate and disconnect the license plate light and turn signal wires
3. Support the stock fender assembly, remove the four bolts and the stock fender assembly.
4. Remove left and right turn signals from stock assembly
5. Install the OEM tag light assembly into the center utilizing the 3 open holes above where the tag sits.
6. Install fender eliminator bracket to subframe using the supplied 6mm nyloc bolts and nuts.
7. Install the stock left and right turn signals into turn signal brackets using the stock turn signal hardware.
8. Route license plate light wiring and turn signal wires through hole under fender eliminator bracket and then under the passenger seat. Reconnect signals and lights.
9. Re-install passenger seat. Check for proper signal and tag light function. Install your license plate.

The purchaser releases Graves Motorsports, Inc. from all liabilities pertaining to the installation and use of purchased parts. Purchaser recognizes that any alteration and/or modifications to the vehicle may increase the risk of injury or accident. This product is intended for Closed Course Competition Use Only and may render the vehicle illegal for use on public roads.