



FEK-20Z650-K

7629 Densmore Ave. Van Nuys, Ca. 91406 | 800-867-6480 | www.gravesport.com

<<<< INSTALLATION OF THIS PRODUCT SHOULD BE PERFORMED BY A QUALIFIED TECHNICIAN >>>>
<<<<<< READ INSTRUCTIONS COMPLETELY BEFORE BEGINNING INSTALLATION >>>>>>

PARTS LIST

Tag Bracket	1	6mm Black washer	4
Signal Mount Assembled	1	6mm Black Nyloc Nuts	4
M6 x 20 Black Button Head Screw	4		

1. Remove the passenger and driver seats to access the 4 main fender bolts.
2. Remove the right and left tail section plastics and disconnect the license plate light and the 2 turn signal wires located on the right side of the subframe.
3. Remove the 4 main fender bolts. Support the stock fender assembly with 1 hand while removing the 1 single Phillips head screw holding the fender in place.
4. Disassemble the stock fender kit and remove the right and left turn signals and the license plate light and its rubber grommets.
5. Install the stock turn signals, license plate light and rubber grommets onto the Graves fender eliminator bracket.
6. Route the license plate light and turn signal wires through the hole under the fender tail section and reconnect them. Check to see that plate light and signals are operating correctly before installing the fender eliminator to the sub frame.
7. Install the fender eliminator to the sub frame using the 4 6x20mm button head screws, the 4 nyloc nuts and washers. Secure in place and install the license plate
8. Reinstall the tail section parts and the seats in the reverse order that you disassembled them.

The purchaser releases Graves Motorsports, Inc. from all liabilities pertaining to the installation and use of purchased parts. Purchaser recognizes that any alteration and/or modifications to the vehicle may increase the risk of injury or accident. This product is intended for Closed Course Competition Use Only and may render the vehicle illegal for use on public roads.