



RSY-14FZ07-A

Adjustable Rearsets Yamaha FZ07 (2015)

PARTS LIST

Left Rearset Assembly	1	8 x 45mm Socket Cap Bolt	1
Right Rearset Assembly	1	8 mm Flanged Nut	1
Aluminum Spacers	4		

<<<<< IT IS RECOMMENDED THAT THIS PRODUCT BE INSTALLED BY A QUALIFIED TECHNICIAN >>>>>

Left Side

1. Loosen shift rod nuts and remove the stock shift rod.
2. Remove the stock rearset bolts, along with the stock heel guard bolts. Keep the bolts for re-installation
3. Install the left rearset assembly to the position desired using the stock bolts and 2 of the supplied aluminum spacers. Torque to standard specs.
4. Reinstall the stock shift rod.
5. Reinstall the left stock heel guard with the stock bolts. Torque to standard specs.

Right Side

1. Remove the stock resreset bolts, stock heelguard bolts, and the stock brake clevis bolt. Keep the bolts for re-installation.
2. Install the right rearset assembly to the position desired using the stock bolts and the remaining 2 supplied aluminum spacers. Torque to standard specs.
3. Reinstall the right stock heel guard with the stock bolts. Torque to standard specs.
4. Reinstall the brake clevis with the supplied 8x45mm socket cap bolt and 8mm flanged nut. **(Photo 1)**



2014 FZ07 Adjustable Rearsets



Photo 1