



www.GRAVESPORT.com
 Tel (818) 902-1942 Fax (818) 902-3821

7629 Densmore Avenue
 Van Nuys, CA 91406

TS401C1

Flush Mount Marker Lights - Clear Replaces most Yamaha turn signals

PARTS LIST

Turn Signal (Left)	1	Nylock Nut 6mm	2
Turn Signal (Right)	1	Aluminum Washer 6mm	2
		Rubber Washer 6mm	2

***** IT IS RECOMMENDED THAT THIS PRODUCT BE INSTALLED BY A QUALIFIED TECHNICIAN *****

REAR TURN SIGNAL INSTALLATION INSTRUCTIONS

- 1) Remove the rear seat/rear seat cowl.
- 2) In order to access the rear turn signal connectors, remove the upper rear tail section and tool kit.
- 3) Locate the rear turn signal connectors (black=right, grey=left) and disconnect.
- 4) Unbolt and remove the stock rear turn signals from the rear fender.
- 5) If installing the new turn signals onto a Graves Motorsports Fender Eliminator Kit, use the included hardware to mount the license plate.
- 6) Install new turn signals onto rear fender. **Do not over tighten turn signal mounting nut. Damage caused by over tightening will not be covered by Graves Motorsports.**
- 7) Thread turn signal connectors up through the wire port and connect wiring harness (black=right, grey=left).
- 8) Test turn signals to ensure proper connection.
- 9) Bundle and secure wires/connectors using the stock zip-tie.
- 10) Re-install the upper rear tail section (if removed).
- 11) Reinstall rear seat/rear seat cowl.

FRONT TURN SIGNAL INSTALLATION INSTRUCTIONS

- 1) In order to access the front turn signal connectors, remove the side fairings.
- 2) Locate the front turn signal connectors (black=right, grey=left) and disconnect.
- 3) Unbolt and remove the stock front turn signals from the side fairings.
- 4) Install new turn signals onto side fairings. **Do not over tighten turn signal mounting nut. Damage caused by over tightening will not be covered by Graves Motorsports.**
- 5) Connect turn signal connectors to wiring harness (black=right, grey=left).
- 6) Test turn signals to ensure proper connection.
- 7) Re-install side fairings.

IMPORTANT

Be sure to test that the marker lights are mounted on the correct sides.

Engage the left side marker to be sure the left side marker lights up.

Engage the right side marker to be sure the right side marker lights up.

The purchaser releases Graves Motorsports, Inc from all liabilities pertaining to the installation and use of purchased parts. Purchaser recognizes that any alteration and/or modifications to the vehicle may increase the risk of injury or accident. **This product is intended for Closed Course Competition Use Only** and may render the vehicle illegal for use on public roads.